# **Interior Signage**

The quintessenz signage system offers a unique monolithic Optic



# **Interior Signage**

With the quintessenz-edgeprofiles, all arrangements are fastened concealed.



# ∑ quintessenz QFA flag signs QFV cover attached QWA - QWV wall signs

#### **Labeling Variants**

#### The Classics QWA - QDA - QFA

They are mostly lacquered and permanently inscribed with slide texts or the digital m-print (material direct print).

#### The Basic Version QWAI - QDAI - QFAI

The aluminum plate is located behind the protective edge for the flat labeling with attached digital printing foils. Together with the foil, the basic version offers flush fit surfaces with an anti-skid protection. To change labels, the old foil is removed and a newly printed foil is glued. All surfaces are silver matt anodised.

#### The Multipurpose QWV - QDV - QFV

Examp

QW

QWA

QWA

QWV

Article

The multipurpose signs have glass covers protecting transparent or paper inlays. They may help to save costs in case of frequent inlay exchange.

e	Standard Measures	Customized Solutions
2 mm Aluminum plains, laquered or anodized. with integrated detachment protection. non-reflecting-Acryl, support variabel caption inlays.	Width 60 cm. The article number indicates merely rounded measures.	installation. Interior lit LED-signs with a depth of only 20 mm.
ple QWA 4260 Quintessenz Wall signposts.	Example QWA 4260 Height 42 cm.	Individule Measures. Special attachment solutions for exterior

## **Mounting Models**

### Wall signs QWA ...

They are equipped with a continuous information carrier on the front side. The special fastening techniques allow flat designs without visible screws.

Banneres QFA ... They are usually wall-mounted elements, which can be seen on both sides in the longitudinal direction of corridors. They are therefore also called booths or nostrils. They are fixed by means of an adapter rail, which allows a wall distance of approx. 20 mm. The design of the banner shields is also suitable for direct mounting as ceiling panels with low false ceilings. The minimum height of 2.100 mm must always be observed!

## Ceiling Signs QDA ...

These signs provide customizable labeling space on both sides. For a celing-hanged installation, they come with integrated fine steel wire as well as comfortably adaptable mounting system which also features a variety of anchors for different celing materials. These are also deliverable seperately.



